

ProFurl SPINEX Top-Down Furler



(Re)discover the joys of asymmetric spinnakers

Rating: Not Rated Yet

Price

1.972,00 €

1.972,00 €

[Ask a question about this product](#)

Manufacturer [ProFurl](#)

Description

(Re)discover the joys of asymmetric spinnakers

Discover the SPINEX, the new solution to furl and unfurl asymmetric spinnakers.

Thanks to the integration of the Sail Bearing Technology developed by Profurl, with a SPINEX system you will be able to operate easily and safely your asymmetric spinnaker.

We recommend our sailing trainings or an [individual training](#) on board of your yacht to learn handling the sail

For further information, dimensions, technical data and options please refer to the product catalogue

- [SPINEX product catalogue](#)
- [NEX product catalogue](#)
- [ProFurl main product catalogue](#)

ADVANTAGES TO USING SPINEX

Endless Furling: ProFurl SPINEX Top-Down Furler

SAIL BEARING TECHNOLOGY: EFFICIENT, RELIABLE FURLING

Problem: Because asymmetric spinnaker cloth is both light and fragile, the anti-twist cable has a tendency to damage it. Also, the cable spins faster than the sail during furling which means the latter sometimes jams.

Profurl solution: A PVC Soft Sleeve that spin freely around the anti-twist cable in order to protect the sail from the cable. Sail Bearing Technology allows you to:

- keep the sail away from the cable
- stop reverse furling, which causes the sail to jam
- reduce wear of the sailcloth
- make furling easier and faster because it has a greater diameter than the cable on its own

A COMPLETE SYSTEM READY TO USE

- SPINEX comes with drum, swivel, cable, end fittings, tack swivel, etc.
- Except for the length of the cable, SPINEX is ready to fit and ready to use out of the box.

MULTI-PURPOSE and adaptable

- Remove the tack swivel and turn your SPINEX into a NEX ready to use with gennakers and code zeros.
- Profurl's SPIN KIT fits on NEX furlers.

OTHER ADVANTAGES:

- Compatible with NEX technology, such as I-Connect, Safe System, etc.
- Improved safety when worked from the cockpit or short-handed.
- Requires little storage space.
- System compatible with all types of asymmetric spinnakers.

Model	SPINEX 0.9	SPINEX 1.5	SPINEX 2.5	SPINEX 4.0
Boat length (ca.)	up to 8 m	up to 10 m	up to 12 m	up to 15 m
Sail area	up to 60 m ²	up to 100 m ²	bis 530 m ²	up to 230 m ²
Working load max.	900 kg	1500 kg	2500 kg	5000 kg
Spool diameter	120 mm	150 mm	180 mm	220 mm
Upper Terminal		Clevis pin snap shakle		
Lower terminal		D shakle		
? Anti-twist cable	9 mm	11 mm	13 mm	15 mm
Cable lenght delivered as standard	14 m	17 m	20 m	25 m
Weight of cables and sleeve/m	0,160 kg	0,210 kg	0,275 kg	0,345 kg