

## AG Neovo X-17P Display



AG Neovo X-17P Front



A brilliant display that delivers advanced design, durability and versatile performance for progressive professional environments

Rating: Not Rated Yet

**Price**

574,00 €

574,00 €

[Ask a question about this product](#)

Manufacturer [AG Neovo](#)

**Description**

The X-17E is a highly durable 17" display that will deliver decades of performance. Featuring NeoV™ Optical Glass, built-in video support and multiple input options, the X-17E is well suited to professional public environments. The strong metal casing and VESA compatible wall mounts allow the X-17E to be mounted just about anywhere. The unique look and versatility of the X-17E make it the perfect display solution for any

modern environment.

**Features:**

<b>Panel</b>	Panel Type: LED-Backlit TFT LCD (TN Technology) Panel Size: 17.0" Max. Resolution: SXGA 1280 x 1024 Pixel Pitch: 0.264 mm Brightness: 250 cd/m <sup>2</sup> Contrast Ratio: 20,000,000:1 (DCR) Viewing Angle (H/V): 170°/160° Display Colour: 16.7M Response Time: 3 ms Surface Treatment: Anti-Glare, 3H
<b>Frequency</b>	Frequency (H): 24 kHz-83 kHz Frequency (V): 50 Hz-75 Hz
<b>Signal Input</b>	DisplayPort: x 1 HDMI: 1.4 x 1 DVI: 24-Pin DVI-D VGA: 15-Pin D-Sub x 1
<b>Audio</b>	Audio In: Stereo Audio Jack (3.5mm) Internal Speakers: 2W x 2 Power Supply: External Power Requirements: DC 12V, 1.58A On Mode: 14W (On) Stand-by Mode: < 0.5W Off Mode: < 0.5W Thickness: 3.0 mm (0.12") Reflection Rate: < 1% Transmission Rate: > 97% Hardness: > 9H
<b>Operating Conditions</b>	Temperature: 0°C-40°C (32°F-104°F) Humidity: 10%-90% (non-condensing)
<b>Storage Conditions</b>	Temperature: -20°C-60°C (-4°F-140°F) Humidity: 5%-95% (non-condensing)
<b>Mounting Stand Security Dimensions</b>	VESA FPMPMI: Yes (100 x 100 mm & 75 x 75 mm) Tilt: 0° to 22° Kensington Security Slot: Yes Product with Base (W x H x D): 409.4 x 398.2 x 175.0 mm (16.1" x 15.7" x 6.9") Product w/o Base (W x H x D): 409.4 x 361.9 x 64.5 mm (16.1" x 15.7" x 2.5") Packaging (W x H x D): 506.0 x 506.0 x 225.0 mm (19.9" x 19.9" x 8.9")
<b>Weight</b>	Product w/o Base: 5.2 kg (11.5 lb) Product with Base: 6.0 kg (13.2 lb) Packaging: 7.5 kg (16.5 lb)
<b>Regulation Approval Accessories</b>	Certifications & Compliance: CE,LVD, RoHS, WEEE, REACH,EAC Supplied: Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card